

10/27/2017



**RELIABILITY MONITOR REPORT  
FOR**

**MFN GST40**

**MAXIM INTEGRATED**

**160 RIO ROBLES  
SAN JOSE, CA 95134**

**This Report was prepared by  
MAXIM INTEGRATED Reliability Engineering**

**Summary:**

The data in the tables that follow was generated as the result of an on-going Process Reliability Monitor. The specific products in this process monitor are:

MAX12000ETB+	MAX2057ETX+	MAX2070GTM+	MAX3814CHJ+	MAX3815CCM+
--------------	-------------	-------------	-------------	-------------

The calculated failure rate for devices using this process is:

**FAILURE RATE:    MTTF (YRS): 107355    QUANTITY: 554    FAILS: 0    FITS: 1.1**

The parameters used to calculate this failure rate are as follows:

**Cf: 60%                    Ea: 0.7                    Tu: 25    °C**

The reliability data follows and in this section is the detailed reliability data by stress. The reliability data section includes the latest data available. This report covers data between 7/1/2017 and 9/30/2017 .

---

**Process Information:**

Process Description:            MFN GST40

---

**OPERATING LIFE**

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	LOT NO.
HIGH TEMP OP LIFE	1607	MAX2070GTM+	135°C	1000 HRS	90	0	NAJYBZ056C
HIGH TEMP OP LIFE	1607	MAX2070GTM+	135°C	1000 HRS	90	0	NAJYBZ056E
HIGH TEMP OP LIFE	1620	MAX12000ETB+	135°C	1000 HRS	80	0	NZD0A3043G
HIGH TEMP OP LIFE	1627	MAX2070GTM+	135°C	1000 HRS	54	0	NAJYBZ056D
HIGH TEMP OP LIFE	1641	MAX3815CCM+	135°C	1000 HRS	48	0	NXQ0A3365AB
HIGH TEMP OP LIFE	1641	MAX3815CCM+	135°C	1000 HRS	32	0	NXQ0A3365AB
HIGH TEMP OP LIFE	1702	MAX3815CCM+	135°C	1000 HRS	48	0	NXQ0AA381AH
HIGH TEMP OP LIFE	1702	MAX3815CCM+	135°C	1000 HRS	32	0	NXQ0AA381AH
HIGH TEMP OP LIFE	1717	MAX2057ETX+	135°C	1000 HRS	48	0	NRE0B3134A
HIGH TEMP OP LIFE	1717	MAX2057ETX+	135°C	1000 HRS	32	0	NRE0B3134A
<b>Total:</b>						<b>0</b>	

---

**STORAGE LIFE**

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	LOT NO.
STORAGE LIFE	1607	MAX2070GTM+	150°C	1000 HRS	90	0	NAJYBZ056D
STORAGE LIFE	1607	MAX2070GTM+	150°C	1000 HRS	89	0	NAJYBZ056E
STORAGE LIFE	1612	MAX3814CHJ+	150°C	1000 HRS	80	0	NBOZBA054H
STORAGE LIFE	1620	MAX12000ETB+	150°C	1000 HRS	80	0	NZD0A3043G
STORAGE LIFE	1641	MAX3815CCM+	150°C	1000 HRS	80	0	NXQ0A3365AB
STORAGE LIFE	1702	MAX3815CCM+	150°C	1000 HRS	80	0	NXQ0AA381AH
STORAGE LIFE	1717	MAX2057ETX+	150°C	1000 HRS	80	0	NRE0B3134A
<b>Total:</b>						<b>0</b>	

---

**TEMPERATURE CYCLE**

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	LOT NO.
TEMP CYCLE, 5' RAMP, 10' DWELL	1607	MAX2070GTM+	-65C TO +150C (Condition C)	1000 CYS	120	0	NAJYBZ056C
TEMP CYCLE, 5' RAMP, 10' DWELL	1607	MAX2070GTM+	-65C TO +150C (Condition C)	500 CYS	120	0	NAJYBZ056D
TEMP CYCLE, 5' RAMP, 10' DWELL	1607	MAX2070GTM+	-65C TO +150C (Condition C)	1000 CYS	120	0	NAJYBZ056E
TEMP CYCLE, 5' RAMP, 10' DWELL	1612	MAX3814CHJ+	-65C TO +150C (Condition C)	1000 CYS	79	0	NBOZBA054H
TEMP CYCLE, 5' RAMP, 10' DWELL	1620	MAX12000ETB+	-65C TO +150C (Condition C)	1000 CYS	80	0	NZD0A3043G
TEMP CYCLE, 5' RAMP, 10' DWELL	1641	MAX3815CCM+	-65C TO +150C (Condition C)	1000 CYS	80	0	NXQ0A3365AB
TEMP CYCLE, 5' RAMP, 10' DWELL	1702	MAX3815CCM+	-65C TO +150C (Condition C)	1000 CYS	80	0	NXQ0AA381AH
TEMP CYCLE, 5' RAMP, 10' DWELL	1717	MAX2057ETX+	-65C TO +150C (Condition C)	1000 CYS	80	0	NRE0B3134A
<b>Total:</b>						<b>0</b>	

---

**TEMPERATURE HUMIDITY BIAS**

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	LOT NO.
BIASED MOISTURE	1620	MAX12000ETB+	130C, 85%	96 HRS	60	0	NZD0A3043G
BIASED MOISTURE	1620	MAX12000ETB+	130C, 85%	96 HRS	20	0	NZD0A3043G
BIASED MOISTURE	1641	MAX3815CCM+	130C, 85%	96 HRS	40	0	NXQ0A3365AB
BIASED MOISTURE	1641	MAX3815CCM+	130C, 85%	96 HRS	40	0	NXQ0A3365AB
BIASED MOISTURE	1702	MAX3815CCM+	130C, 85%	96 HRS	40	0	NXQ0AA381AH
BIASED MOISTURE	1702	MAX3815CCM+	130C, 85%	96 HRS	40	0	NXQ0AA381AH
BIASED MOISTURE	1717	MAX2057ETX+	130C, 85%	96 HRS	40	0	NRE0B3134A
BIASED MOISTURE	1717	MAX2057ETX+	130C, 85%	96 HRS	40	0	NRE0B3134A
<b>Total:</b>						<b>0</b>	

**FAILURE RATE: MTTF (YRS): 107355 QUANTITY: 554 FAILS: 0 FITS: 1.1**