

A

UNLESS OTHERWISE SPECIFIED

1. DIMENSIONS ARE IN INCHES (EXCEPT WHERE NOTED).

2. MATERIAL: [USE CHECKED ITEMS FOR MATERIAL]

3. BOARD MATERIAL:

(X) ISOLA 370HR OR EQUIVALENT

() ISOLA-IT408HR OR EQUIVALENT

() NCLCO-4000-13

() MEGTRON 6

() ROGERS 4308

() ROGERS 4003C

() OTHER -----

3. THE PCB SHALL BE FABRICATED TO IPC-6012, TYPE X, CLASS 2.

WORKMANSHIP SHALL CONFORM TO IPC-A-600, CLASS 2, CURRENT REVISIONS.

4. BOARD MATERIAL & CONSTRUCTION SHALL MEET THE REQUIREMENTS OF UL796 WITH FLAMMABILITY RATING OF 94V-0.

5. OVERALL BOARD THICKNESS REFER TO LAMINATION DIAGRAM. TOLERANCE APPLIES AFTER ALL LAMINATION AND PLATING OPERATIONS. IT IS TO BE MEASURED FROM TOP PCB METAL TO BOTTOM PCB METAL UNLESS OTHERWISE SPECIFIED.

6. BOW & TWIST NOT TO EXCEED 0.0075 IN. (0.75%) PER LINEAR INCH.

BOW & TWIST SHOULD BE MEASURED PER IPC-1M-650, METHOD 2.4.22.

TOOLING: [USE CHECKED ITEMS FOR TOOLING]

7. PHOTO ETCH CIRCUITRY PER ENCLOSED GERBER RS274X OR ODB++ FORMAT FILE.

DRILL LOCATION AND SIZE CONTROLLED BY EXCELLON CNC DRILL FILE.

8. IF STATED IN THE LAMINATION DIAGRAM, THE DIELECTRIC THICKNESS OF ANY CONTROLLED IMPEDANCE LAYER IS FOR REFERENCE ONLY. FINAL ACCEPTANCE SHALL BE DETERMINED BY THESE LAYERS HAVING A CHARACTERISTIC IMPEDANCE OF +/-10% OHMS AS STATED IN THE LAMINATION DIAGRAM. THE VENDOR CAN MAKE ADJUSTMENTS AS LONG AS THE STATED IMPEDANCE AND OVERALL BOARD THICKNESS IS MAINTAINED, ANY ADJUSTMENT MADE TO TRACE WIDTH OR SPACING MUST HAVE PRIOR WRITTEN APPROVAL FROM MAXIM.

9. ALL TRACES FILLETED OPTION TO ENHANCE RELIABILITY AT PAD JUNCTIONS WHERE SPACING PERMITS. UNLESS OTHERWISE SPECIFIED:

() FILLETED

(X) NOT FILLETED

10. LAYER TO LAYER REGISTRATIONS SHALL BE WITHIN .003 INCHES.

LEGEND TO LEGEND +/- 0.007 INCHES

FINISH: [USE CHECKED ITEMS FOR FINISHING]

11. PLATING SPECIFICATION:

(X) STARTING COPPER WEIGHT FOR OUTER LAYERS TO BE [1 OZ]. THE FINISH COPPER WEIGHT IS [1 OZ].

FOR OUTER LAYERS WHERE SPACING PREVENTS THE USE OF [1 OZ] AS A STARTING WEIGHT THE STARTING WEIGHT CAN BE (0.5 OZ) AS LONG AS THE FINISH COPPER WEIGHT IS [1 OZ] UNLESS OTHERWISE SPECIFIED

() STARTING COPPER WEIGHT FOR OUTER LAYERS TO BE [1 OZ]. THE FINISH COPPER WEIGHT IS [2 OZ].

FOR OUTER LAYERS WHERE SPACING PREVENTS THE USE OF [1 OZ] AS A STARTING WEIGHT, THE STARTING WEIGHT CAN BE (0.5 OZ) AS LONG AS THE FINISH COPPER WEIGHT IS [2 OZ]. UNLESS OTHERWISE SPECIFIED

() STARTING COPPER WEIGHT FOR OUTER LAYERS TO BE [2 OZ]. THE FINISH COPPER WEIGHT IS [2 OZ]M

FOR OUTER LAYERS WHERE SPACING PREVENTS THE USE OF [2 OZ] AS A STARTING WEIGHT, THE STARTING WEIGHT CAN BE (<2 OZ) AS LONG AS THE FINISH COPPER WEIGHT IS [2 OZ]. UNLESS OTHERWISE SPECIFIED

() OTHER -----

12. CHECK ALL THAT APPLY

() ELECTRODEPOSITED HARD GOLD PLATE, TYPE 1 (99.7% MIN GOLD), GRADE C (KNOOF HARDNESS 130-200), CLASS 1 (50-100 MICRO INCHES THICK) IN ACCORDANCE WITH MIL-C-45 GENERAL SURFACING REQUIREMENTS MUST MEET ANSI/IPC-A-600 (CURRENT REV.) SECTION 4.0, CLASS 3 (50-100 MICROINCHES THICK) OVER ELECTRODEPOSITED NICKEL PLATE IN ACCORDANCE WITH ANSI/IPC-A-6000, SECTION 4.0, CLASS 3 (200-600 MICROINCHES THICK).

(X) FINISH CONDUCTOR SURFACES: IMMERSION GOLD, 3-8 MICRO INCHES OVER 100 MICRO INCHES MINIMUM OF ELECTROLESS NICKEL.

() FINISH CONDUCTOR SURFACES: IMMERSION GOLD, 2-5 MICRO INCHES OVER 118-236 MICRO INCHES MINIMUM OF ELECTROLESS NICKEL.

() FINGERS TO BE GOLD PLATED.

() LEAD FREE AND RnHS COMPLIANT PLATING.

() OTHER -----

13. DRILL SIZES ARE FINISHED HOLE SIZES. ALL HOLES SHALL BE LOCATED WITHIN .005 DTP. MINIMUM BARREL PLATING OF .001 IN. PLATED HOLES SHALL NOT BE ROUGH OR IRREGULAR SO AS TO HINDER PROPER SOLDER WICKING.

14. CHECK ALL THAT APPLY

() GREEN SOLDERMASK OVER BARE COPPER/BARE GOLD (BOTTOM SIDE ONLY) WITH LIQUID PHOTO IMAGEABLE PER ARTWORK.

(X) GREEN TAIYO PSR-4000

() OTHERS: BLACK SOLDERMASK (BOTTOM SIDE ONLY)

15. CHECK ALL THAT APPLY

(X) APPLY SILKSREEN USING A NON-CONDUCTIVE, WHITE EPOXY BASED INK PER ARTWORK.

() OTHER -----

() VENDOR LOGO & DATE CODE REQUIRED IN INK ON BOTTOM SIDE ONLY. DATE CODE FORMAT MUST BE YYYY

TESTING:

17. FINAL ELECTRICAL TEST TO BE PERFORMED USING IPC-D-356A NETLIST OR ODB++ FORMAT FILE. (REQUIRED UNLESS OTHERWISE SPECIFIED IN QUOTE)

THE PCB SHALL HAVE A VERIFICATION STAMP.

18. A TIME DOMAIN REFLECTOMETER REPORT FOR EACH IMPEDANCE CONTROLLED LAYER AND A CERTIFICATE OF COMPLIANCE SHALL BE PROVIDED BY VENDOR AT TIME OF SHIPMENT.

MISCELLANEOUS:

IF PRESENT, ALL BLIND/BURIED VIAS WITH AN ASPECT RATIO <1:1 TO BE PLATED SHUT WITH COPPER WHEN USED AS VIA-IN-PAID OR AS A STAKED VIA. BLIND/BURIED VIAS WITH AN ASPECT RATIO >1:1 TO BE FILLED WITH NON-CONDUCTIVE EPOXY. UNLESS OTHERWISE SPECIFIED.

20. FOR ALL DRILL INFORMATION REFER TO DRILL CHART.

(X) NON-CONDUCTIVE EPOXY: FILL AND CAP ALL 0.004 INCH DRILLED VIAS.

() SILVER: FILL AND CAP ALL 0.00XX INCH DRILLED VIAS.

21. FINISHED SURFACE CONTACTS AND FILLED VIAS TO BE FREE OF ANY PITS, SCRATCHES PROBE MARKS OR OTHER DEFORMITIES THAT COULD EFFECT THE APPEARANCE AND PERFORMANCE OF THE CONTACT SURFACE. CONTACTS ARE TO BE AS FLAT AS POSSIBLE. NOT TO EXCEED +/- 0.001" OF FLATNESS.

22. THIEVING:

() SUPPLIER MAY ADD THIEVING TO COMPENSATE FOR LOW COPPER DENSITY AREAS ON THIS DESIGN.


(X) SUPPLIER MAY NOT ADD THIEVING TO COMPENSATE FOR LOW COPPER DENSITY AREAS ON THIS DESIGN.

23. PENMUT






() PENMUTS TO BE INSTALLED BY SUPPLIER.


() PENMUTS NOT TO BE INSTALLED BY SUPPLIER.

(X) NOT APPLICABLE



BOTTOM SIDE REQUIRES BLACK SOLDERMASK

DRILL CART: TOP to BOTTOM					
ALL UNITS ARE IN MILS					
FIGURE	SIZE	TOLERANCE	PLATED	QTY	NOTES
	4.0	+0.0/- .4.0	PLATED 3	3	
	6.0	+3.0/- .4.0	PLATED	50	
	8.0	+3.0/- .6.0	PLATED	1	
	8.0	+3.0/- .6.0	PLATED	1	
	12.01	+3.0/- .3.0	PLATED	17	

TOLERANCES UNLESS OTHERWISE SPECIFIED		THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO MAXIM. THE INFORMATION IN THIS DOCUMENT IS NOT TO BE SHOWN, REPRODUCED, OR DISCLOSED TO ANYONE OUTSIDE OF MAXIM WITHOUT PRIOR WRITTEN PERMISSION FROM MAXIM.		<div><div>maxim integrated™</div></div>	
FRACTIONS DECIMALS ANGLES +/- $\frac{\quad}{\quad}$.XX +/- .01 .XXX +/- .005 +/- $\frac{\quad}{\quad}$				HARDWARE NAME:	
MATERIAL:				MAX86140_OSB_EVKIT_A	
SEE NOTES		DRAWN BY: NGUYEN NGUYEN DATE: 04/20/2017		HARDWARE NUMBER:	
FINISH:		CHECKED BY: DATE:		xx-xxxxx-xxx	
SEE NOTES		APPR. BY: DATE:		NOT TO SCALE	
		APPR. BY: DATE:		TEMPLATE REV: 2.1	
				SHEET 1 OF 1	