



SONOMA (MAXREFDES14#)	
P/N: EPCBREFDES14	REV C
	
LAYER	DRILL & MECHANICALS
ALL UNITS ARE IN 0.001"	



SIZE	QTY	SYM	PLATED	TOL
45	12	+	YES	+/-3.0
25	14	X	YES	+/-3.0
15	58	□	YES	+/-3.0
50	4	◇	YES	+/-3.0

## NOTES: UNLESS OTHERWISE SPECIFIED

- FABRICATE USING PROVIDED GERBER FILES PER LATEST REVISION OF IPC-A-600 UNLESS OTHERWISE NOTED.
- MATERIAL: RoHS COMPLIANT FR-408 OR SIMILAR LAMINATE MATERIAL WITH  $T_g \geq 170$  AND COMPATIBLE WITH LEAD-FREE SOLDERING PROCESS.
- BOARD DIMENSIONS: 3.30"X0.80"  $\pm$  0.010".  
BOARD THICKNESS: 0.062".
- LAYERS: 2.
- MINIMUM TRACE/SPACING: 10 MILS/8MILS.
- COPPER CLAD FINISH: 1oz MINIMUM ON ALL LAYERS.
- SURFACE MOUNT PADS: 108.
- SOLDERMASK: GREEN LPI SMOBC.
- LEGENDS: WHITE. DOUBLE-SIDED. NON-CONDUCTIVE EPOXY INK OR EQUIVALENT. CLIPPED ALL LEGENDS FROM EXPOSED METAL.
- PLATING: MUST BE LEAD FREE AND RoHS COMPLIANT.
- FINISH: VENDOR SHOULD USE THE MOST ECONOMICAL LEAD FREE AND RoHS COMPLIANT PROCESS AVAILABLE OR AS SPECIFIED IN PURCHASE ORDER.  
APPROVED FINISH:  
HASL LEAD-FREE  
IMMERSION TIN  
IMMERSION GOLD
- VENDOR LOGO & DATE CODE IN INK ON BOTTOM SIDE ONLY. DATE CODE FORMAT MUST BE YYWW ONLY.
- THRU HOLES: 0.001" MIN.
- TOLERANCES:  
PLATED-THRU HOLES:  $\pm 0.003$ "  
PATTERN-TO-PATTERN:  $\pm 0.005$ "  
LEGEND TO LEGEND:  $\pm 0.007$ "  
SOLDERMASK TO PATTERN:  $\pm 0.005$ "