

D

C

B




A


D

C

B


A

8	7	6	5	4	3	2	1																																			
						<table><tr><th colspan="4">REVISIONS</th></tr><tr><th>REV</th><th>DESCRIPTION</th><th>APPROVED</th><th>DATE</th></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr></table>	REVISIONS				REV	DESCRIPTION	APPROVED	DATE																												
REVISIONS																																										
REV	DESCRIPTION	APPROVED	DATE																																							
						<p>NOTES:</p> <p>UNLESS OTHERWISE SPECIFIED</p> <p>1. DIMENSIONS ARE IN INCHES (EXCEPT WHERE NOTED).</p> <p>MATERIAL: (USE CHECKED ITEMS FOR MATERIAL)</p> <p>2. BOARD MATERIAL:</p> <p>(X) ISOLA 370HR OR EQUIVALENT</p> <p>() ISOLA-FR408HR OR EQUIVALENT</p> <p>() NELCO-4000-13</p> <p>() MEGTRON 6</p> <p>() ROGERS 4350B</p> <p>() ROGERS 4003C</p> <p>() OTHER -----</p> <p>3. THE PCB SHALL BE FABRICATED TO IPC-6012, TYPE X, CLASS 2. WORKMANSHIP SHALL CONFORM TO IPC-A-600, CLASS 2, CURRENT REVISIONS.</p> <p>4. BOARD MATERIAL & CONSTRUCTION SHALL MEET THE REQUIREMENTS OF UL796 WITH FLAMMABILITY RATING OF 94V-0.</p> <p>5. OVERALL BOARD THICKNESS REFER TO LAMINATION DIAGRAM. TOLERANCE APPLIES AFTER ALL LAMINATION AND PLATING PROCESSES. IT IS TO BE MEASURED FROM TOP PCB METAL TO BOTTOM PCB METAL UNLESS OTHERWISE SPECIFIED.</p> <p>6. BOW & TWIST NOT TO EXCEED 0.0075 IN. (0.75%) PER LINEAR INCH. BOW & TWIST SHOULD BE MEASURED PER IPC-TM-650, METHOD 2.4.22.</p> <p>TOOLING:</p> <p>(USE CHECKED ITEMS FOR TOOLING)</p> <p>7. PHOTO ETCH CIRCUITRY PER ENCLOSED GERBER RS274X OR ODB++ FORMAT FILE. DRILL LOCATION AND SIZE CONTROLLED BY EXCELLON CNC DRILL FILE.</p> <p>8. IMPEDANCE REQUIREMENTS: IF NO STACKUP IS DEFINED, THE VENDOR IS ALLOWED TO ADJUST THE DIELECTRIC THICKNESS AND TRACE WIDTHS TO MEET THE IMPEDANCE REQUIREMENT. IF SPECIFIED, VENDOR MUST FOLLOW AND MEET THE REQUIREMENTS LISTED IN THE IMPEDANCE TABLE. ANY ADJUSTMENTS MADE TO THE DEFINED STACKUP, TRACE WIDTH & SPACING THAT IMPACT THE REQUIREMENTS MUST HAVE WRITTEN APPROVAL FROM MAXIM.</p> <p>9. ALL TRACES FILLETED OPTION TO ENHANCE RELIABILITY AT PAD JUNCTIONS WHERE SPACING PERMITS. UNLESS OTHERWISE SPECIFIED:</p> <p>() FILLETED</p> <p>(X) NOT FILLETED</p> <p>10. LAYER TO LAYER REGISTRATIONS SHALL BE WITHIN .003 INCHES. LEGEND TO LEGEND +/- 0.007 INCHES.</p> <p>FINISH:</p> <p>(USE CHECKED ITEMS FOR PLATING)</p> <p>11. FINISHED COPPER WEIGHT/THICKNESS:</p> <p>(X) REFER TO LAMINATION DIAGRAM FOR FINISHED COPPER WEIGHT/THICKNESS REQUIREMENTS. THE STARTING COPPER WEIGHT/THICKNESS CAN VARY AS LONG AS THE FINISHED COPPER WEIGHT/THICKNESS IS NOT LESS THAN THE SPECIFIED VALUE. UNLESS OTHERWISE SPECIFIED.</p> <p>() OTHER -----</p> <p>12. CHECK ALL THAT APPLY</p> <p>() ELECTRODEPOSITED HARD GOLD PLATE, TYPE 1 (99.7% MIN GOLD), GRADE C (KNOOP HARDNESS 130-200), CLASS 1 (50-100 MICRO INCHES THICK) IN ACCORDANCE WITH MIL-G-45204C. GENERAL SURFACING REQUIREMENTS MUST MEET ANSI/IPC-A-600(CURRENT REV) SECTION 4.0, CLASS 3 (50-100 MICROINCHES THICK) OVER ELECTRODEPOSITED NICKEL PLATE IN ACCORDANCE WITH ANSI/IPC-A-600D, SECTION 4.0, CLASS 3 (200-600 MICROINCHES THICK).</p> <p>() FINISH CONDUCTOR SURFACES: IMMERSION GOLD, 3-8 MICRO INCHES OVER 100 MICRO INCHES MINIMUM OF ELECTROLESS NICKEL.</p> <p>() FINISH CONDUCTOR SURFACES: IMMERSION GOLD, 2-5 MICRO INCHES OVER 118-236 MICRO INCHES MINIMUM OF ELECTROLESS NICKEL.</p> <p>() FINGERS TO BE GOLD PLATED.</p> <p>(X) LEAD FREE AND RoHS COMPLIANT PLATING.</p> <p>() OTHER -----</p> <p>13. DRILL SIZES ARE FINISHED HOLE SIZES. ALL HOLES SHALL BE LOCATED WITHIN .005 DTP. MINIMUM BARREL PLATING OF .001 IN. PLATED HOLES SHALL NOT BE ROUGH OR IRREGULAR SO AS TO HINDER PROPER SOLDER WICKING.</p> <p>14. CHECK ALL THAT APPLY</p> <p>(X) GREEN SOLDERMASK OVER BARE COPPER/BARE GOLD (BOTH SIDES) WITH LIQUID PHOTO IMAGEABLE INK (LPI) PER ARTWORK.</p> <p>() GREEN TAIYO PSR-4000</p> <p>() OTHER -----</p> <p>15. CHECK ALL THAT APPLY</p> <p>(X) APPLY SILKSCREEN USING A NON-CONDUCTIVE, WHITE EPOXY BASED INK PER ARTWORK.</p> <p>() OTHER -----</p> <p>16. VENDOR LOGO & DATE CODE REQUIRED IN LEGEND ON BOTTOM SIDE ONLY. DATE CODE FORMAT MUST BE YYYY ONLY IF NO BOTTOM LEGEND SUPPLIED. VENDOR CAN CREATE BOTTOM LEGEND LAYER TO ADD LOGO & DATE CODE.</p> <p>TESTING:</p> <p>17. FINAL ELECTRICAL TEST TO BE PERFORMED USING PROVIDED IPC-D-356A NETLIST OR ODB++ FORMAT FILE. (REQUIRED UNLESS OTHERWISE SPECIFIED IN QUOTE)</p> <p>THE PCB SHALL HAVE A VERIFICATION STAMP.</p> <p>18. A TIME DOMAIN REFLECTOMETER REPORT FOR EACH IMPEDANCE CONTROLLED LAYER AND A CERTIFICATE OF COMPLIANCE SHALL BE PROVIDED BY VENDOR AT TIME OF SHIPMENT. INSTANCES WHERE TDR TESTING CAN'T BE PERFORMED BECAUSE THE TRACE LENGTH IS TOO SHORT ON THE OUTER LAYERS AT THE PIN ESCAPES IS ACCEPTABLE, ALL OTHER INSTANCES MUST BE REPORTED.</p> <p>MISCELLANEOUS:</p> <p>19. IF PRESENT, ALL BLIND/BURIED VIAS WITH AN ASPECT RATIO >1:1 TO BE PLATED SHUT WITH COPPER WHEN USED AS VIA-IN PAD OR AS A STACKED VIA. BLIND/BURIED VIAS WITH AN ASPECT RATIO >1:1 TO BE FILLED WITH NON-CONDUCTIVE EPOXY, UNLESS OTHERWISE SPECIFIED.</p> <p>20. FOR ALL DRILL INFORMATION REFER TO DRILL CHART.</p> <p>() NON-CONDUCTIVE EPOXY, FILL AND CAP ALL 0.0XXX INCH DRILLED VIAS.</p> <p>() SILVER: FILL AND CAP ALL 0.0XXX INCH DRILLED VIAS.</p> <p>21. FINISHED SURFACE CONTACTS AND FILLED VIAS TO BE FREE OF ANY PITS, SCRATCHES PROBE MARKS OR OTHER DEFORMITIES THAT COULD EFFECT THE APPEARANCE AND PERFORMANCE OF THE CONTACT SURFACE. CONTACTS ARE TO BE AS FLAT AS POSSIBLE, NOT TO EXCEED +/- 0.001" OF FLATNESS.</p> <p>22. THIEVING:</p> <p>() SUPPLIER MAY ADD THIEVING TO COMPENSATE FOR LOW COPPER DENSITY AREAS ON THIS DESIGN.</p> <p>(X) SUPPLIER MAY NOT ADD THIEVING TO COMPENSATE FOR LOW COPPER DENSITY AREAS ON THIS DESIGN.</p> <p>23. PENNUT</p> <p>() FLUSH MOUNT PENNUTS TO BE INSTALLED BY FABRICATOR.</p> <p>() NON-FLUSH MOUNT PENNUTS TO BE INSTALLED BY ASSEMBLY.</p> <p>(X) NOT APPLICABLE.</p>																																				
						<table><tr><th colspan="3">TOLERANCES UNLESS OTHERWISE SPECIFIED</th></tr><tr><td>FRACTIONS</td><td>DECIMALS</td><td>ANGLES</td></tr><tr><td>$\frac{XX}{XXX}$</td><td>.XX +/- .01 .XXX +/- .005</td><td>\angle +/- $\frac{XX}{XXX}$</td></tr><tr><td colspan="3">MATERIAL:</td></tr><tr><td colspan="3">SEE NOTES</td></tr><tr><td colspan="3">FINISH:</td></tr><tr><td colspan="3">SEE NOTES</td></tr></table>	TOLERANCES UNLESS OTHERWISE SPECIFIED			FRACTIONS	DECIMALS	ANGLES	$\frac{XX}{XXX}$.XX +/- .01 .XXX +/- .005	\angle +/- $\frac{XX}{XXX}$	MATERIAL:			SEE NOTES			FINISH:			SEE NOTES																	
TOLERANCES UNLESS OTHERWISE SPECIFIED																																										
FRACTIONS	DECIMALS	ANGLES																																								
$\frac{XX}{XXX}$.XX +/- .01 .XXX +/- .005	\angle +/- $\frac{XX}{XXX}$																																								
MATERIAL:																																										
SEE NOTES																																										
FINISH:																																										
SEE NOTES																																										
						<table><tr><td colspan="2">THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO MAXIM. THE INFORMATION IN THIS DOCUMENT IS NOT TO BE SHOWN, REPRODUCED, OR DISCLOSED TO ANYONE OUTSIDE OF MAXIM WITHOUT PRIOR WRITTEN PERMISSION FROM MAXIM.</td><td colspan="2"></td></tr><tr><td colspan="2">HARDWARE NAME:</td><td colspan="2">MAXI17503_EMI_EVKIT_C</td></tr><tr><td colspan="2">DRAWN BY: MS</td><td colspan="2">DATE: 07/11/2018</td></tr><tr><td colspan="2">CHECKED BY:</td><td colspan="2">DATE:</td></tr><tr><td colspan="2">APPR. BY:</td><td colspan="2">DATE:</td></tr><tr><td colspan="2">APPR. BY:</td><td colspan="2">DATE:</td></tr><tr><td colspan="2">HARDWARE NUMBER:</td><td colspan="2">XX-XXXX-XXX</td></tr><tr><td colspan="2">NOT TO SCALE</td><td colspan="2">TEMPLATE REV:</td></tr><tr><td colspan="2">SHEET 1 OF 1</td><td colspan="2">REV C</td></tr></table>	THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO MAXIM. THE INFORMATION IN THIS DOCUMENT IS NOT TO BE SHOWN, REPRODUCED, OR DISCLOSED TO ANYONE OUTSIDE OF MAXIM WITHOUT PRIOR WRITTEN PERMISSION FROM MAXIM.				HARDWARE NAME:		MAXI17503_EMI_EVKIT_C		DRAWN BY: MS		DATE: 07/11/2018		CHECKED BY:		DATE:		APPR. BY:		DATE:		APPR. BY:		DATE:		HARDWARE NUMBER:		XX-XXXX-XXX		NOT TO SCALE		TEMPLATE REV:		SHEET 1 OF 1		REV C	
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO MAXIM. THE INFORMATION IN THIS DOCUMENT IS NOT TO BE SHOWN, REPRODUCED, OR DISCLOSED TO ANYONE OUTSIDE OF MAXIM WITHOUT PRIOR WRITTEN PERMISSION FROM MAXIM.																																										
HARDWARE NAME:		MAXI17503_EMI_EVKIT_C																																								
DRAWN BY: MS		DATE: 07/11/2018																																								
CHECKED BY:		DATE:																																								
APPR. BY:		DATE:																																								
APPR. BY:		DATE:																																								
HARDWARE NUMBER:		XX-XXXX-XXX																																								
NOT TO SCALE		TEMPLATE REV:																																								
SHEET 1 OF 1		REV C																																								
8	7	6	5	4	3	2	1																																			



LAMINATION DIAGRAM				
LAYER NUMBER	LAYER NAME	COPPER THICKNESS (OZ./INCH)	DIELECTRIC THICKNESS (IN.)	DIELECTRIC MATERIAL
1	TOP	1 OZ. 0.0014" MIN		FOIL
2	L2_GND	1 OZ. 0.0014"	T80	ISOLA 370HR/EQUIVALENT
3	L3_GND	1 OZ. 0.0014"	T80	ISOLA 370HR/EQUIVALENT
4	BOTTOM	1 OZ. 0.0014" MIN	T80	ISOLA 370HR/EQUIVALENT
FOIL				
THE FINISHED PCB THICKNESS TO BE: 0.062" +/- 0.010"				

DRILL CHART: TOP to BOTTOM					
ALL UNITS ARE IN MILS					
FIGURE	SIZE	TOLERANCE	PLATED	QTY	NOTES
△	18.0	+3.0/-16.0	PLATED	78	
①	39.37	+3.0/-3.0	PLATED	18	
②	45.28	+3.0/-3.0	PLATED	9	
③	125.0	+3.0/-3.0	PLATED	4	

TOLERANCES UNLESS OTHERWISE SPECIFIED		THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO MAXIM. THE INFORMATION IN THIS DOCUMENT IS NOT TO BE SHOWN, REPRODUCED, OR DISCLOSED TO ANYONE OUTSIDE OF MAXIM WITHOUT PRIOR WRITTEN PERMISSION FROM MAXIM.		 maxim integrated™	
FRACTIONS		DECIMALS	ANGLES	HARDWARE NAME:	
$\frac{XX}{XXX}$.XX +/- .01 .XXX +/- .005	\angle +/- $\frac{XX}{XXX}$	MAXI17503_EMI_EVKIT_C	
MATERIAL:		SEE NOTES	DRAWN BY: MS	DATE: 07/11/2018	
FINISH:		SEE NOTES	CHECKED BY:	DATE:	
			APPR. BY:	DATE:	
			APPR. BY:	DATE:	
			HARDWARE NUMBER:	XX-XXXX-XXX	
			NOT TO SCALE	TEMPLATE REV:	
			SHEET 1 OF 1	REV C	