




MAXREFDES73#	
WASP GSR	
P/N: EPCBREFDES73	REV A
 maxim integrated™	
LAYER DRILL & MECHANICALS	
DATE:	ALL UNITS ARE IN 0.001"



SIZE	QTY	SYM	PLATED	TOL
59.06	4	+	NO	+/-3.0
12	63	×	YES	+/-3.0
6	76	□	YES	+/-3.0
45	2	◇	YES	+/-3.0
20	3	⊗	YES	+/-3.0
23.62	2	⊗	NO	+/-3.0

NOTES: UNLESS OTHERWISE SPECIFIED

- FABRICATE USING PROVIDED GERBER FILES PER LATEST REVISION OF IPC-A-600 UNLESS OTHERWISE NOTED.
- MATERIAL: RoHS COMPLIANT FR-408 AND COMPATIBLE WITH LEAD-FREE SOLDERING PROCESS.
- BOARD DIMENSIONS: 1.48" x 1.40" ±0.010".
BOARD THICKNESS: 0.062"
- LAYERS: 6.
- MINIMUM TRACE/SPACING: 3MILS/3MILS.
- COPPER CLAD FINISH: 1oz ON OUTER LAYERS AND 1oz ON INNER LAYERS.
- SURFACE MOUNT PADS: 346.
- SOLDERMASK: GREEN TAIYO PSR-4000.
SOLDERMASK APERTURE TOLERANCE: ±0.0005".
- LEGENDS: WHITE. DOUBLE-SIDED. NON-CONDUCTIVE EPOXY INK OR EQUIVALENT.
CLIPPED ALL LEGENDS FROM EXPOSED METAL.
- PLATING: MUST BE LEAD FREE AND RoHS COMPLIANT.
- FINISH: 3-8u" IMMERSION Au OVER 100u" Ni.
- VENDOR LOGO & DATE CODE IN INK ON BOTTOM SIDE ONLY. DATE CODE FORMAT MUST BE YYWW ONLY.
- THRU HOLES: 0.001" MIN.
- TOLERANCES:
PLATED-THRU HOLES: ±0.003"
PATTERN-TO-PATTERN: ±0.005"
LEGEND TO LEGEND: ±0.007"



CROSS SECTION DETAIL