



## Initial Design


1.0

### Design Requirements

---

Parameter	Value
Minimum Input Voltage	4.5V
Maximum Input Voltage	5.5V
Nominal Input Voltage	5V
Input Voltage Ripple	1%
Output Voltage	1.8V
Output Current	2A
Output Voltage Ripple	1%
Load Step Start Current	1A
Load Step Current	2A
Load Step Edge Rate	5A/us
Output Voltage Load Step Over/Undershoot	5%
Performance Priority	Balance Efficiency and Size
BOM Priority	Cost
Inductor Current Ratio (LIR)	0.3
Compensator Type	Type II: One less capacitor

## Schematic



If the current level (starting current for Load Steps) is too low, AC, Steady State and Load Step analyses may fail due to skip mode operation


## BOM

Ref	Qty	Part Number	Manufacturer	Description
U1	1	MAX15066EWE+T	Maxim Integrated	High-Efficiency, 4A, Step-Down DC-DC Regulator with Internal Power Switches
C1	2	GRM32ER71E226ME15	Murata	Cap Ceramic 22uF 25V 1210 125C
C2	1	C4532X7R2J104K230KA	TDK	Cap Ceramic 0.1uF 630V X7R 10% Pad SMD 1812 125°C T/R
C3	1	08051C682KAT2A	AVX	Cap Ceramic 0.0068uF 100V X7R 10% Pad SMD 0805 125°C T/R
C5	1	C2012X7R2E103K125AA	TDK	Cap Ceramic 0.01uF 250V X7R 10% Pad SMD 0805 125°C T/R
C7	2	C4532X7R1C336M250KC	TDK	Cap Ceramic 33uF 16V X7R 20% SMD 1812 125C Plastic T/R
C8	1	0201YC151KAT2A	AVX	Cap Ceramic 150pF 16V X7R 10% Pad SMD 0201 125°C T/R
C10	1	C2012X7R2E103K125AA	TDK	Cap Ceramic 0.01uF 250V X7R 10% Pad SMD 0805 125°C T/R
C11	1	C5750X7R2E105K230KA	TDK	Cap Ceramic 1uF 250V X7R 10% Pad SMD 2220 125°C T/R
L1	1	CLF6045T-3R3N	TDK	Inductor 3.3uH 30% 19mOhm 3.1A Isat 3.5A Irms
R1	1	TFCR0603-10W-E-1962FT	Venkel	Res Thin Film 0603 19.6K Ohm 1% 0.1W(1/10W) ±25ppm/°C Pad SMD T/R

R2	1	CPF0603F10KC1	TE Connectivity	Res Thin Film 0603 10K Ohm 1% 0.063W(1/16W) ±50ppm/°C Epoxy Pad SMD T/R
R3	1	TFCR0603-16W-E-4321FT	Venkel	Res Thin Film 0603 4.32K Ohm 1% 0.063W(1/16W) ±25ppm/°C Pad SMD T/R
R5	1	CPF0603F10KC1	TE Connectivity	Res Thin Film 0603 10K Ohm 1% 0.063W(1/16W) ±50ppm/°C Epoxy Pad SMD T/R
R6	1	CPF0603F10KC1	TE Connectivity	Res Thin Film 0603 10K Ohm 1% 0.063W(1/16W) ±50ppm/°C Epoxy Pad SMD T/R
R7	1	CRL0603-FW-1R00ELF	Bourns	Res Thick Film 0603 1 Ohm 1% 0.1W(1/10W) ±200ppm/°C Pad SMD T/R


## Simulation Results

### Efficiency - Mon Nov 19 2018 11:14:08




## POWER LOSS PLOT

Default




## Losses






Component	Loss (W)	% of total
Cin - ESR	0.00184	0.6
Control MOSFET - gate charge	0.0125	3.8
Synchronous MOSFET - diode Vforward during dead time	0.0008	0.2
Cout - ESR	0.000036	0
Control IC - quiescent	0.0055	1.7
Control MOSFET - Rds_on	0.06378	19.3
Synchronous MOSFET - Coss	0.001013	0.3
Control MOSFET - Coss	0.001013	0.3
Control MOSFET - switching	0.043103	13
Synchronous MOSFET - diode reverse recovery	0.0125	3.8
Synchronous MOSFET - Rds_on	0.052726	15.9
Lout - AC + DC	0.123726	37.4
Synchronous MOSFET - gate charge	0.0125	3.8
Total	0.331036	100

AC Loop - Mon Nov 19 2018 11:14:08




Phase Margin: 62.4° at a crossover frequency of 41.1kHz


## Line Transient - Mon Nov 19 2018 11:14:08




## SWITCHING


Default









Steady State - Mon Nov 19 2018 11:14:08




## SWITCHING


Default









Start Up - Mon Nov 19 2018 11:14:08





SWITCHING

Default







**Load Step - Mon Nov 19 2018 11:14:08**

SWITCHING

Default

