



7/20/2007

**RELIABILITY MONITOR REPORT
FOR**

uSOP Package

Dallas Semiconductor

**4401 South Beltwood Parkway
Dallas, TX 75244-3292**

**This Report was prepared by
Dallas Semiconductor Reliability Engineering**

Summary:

The data in the tables that follow was generated as the result of an on-going Package Reliability Monitor. The assemblies covered by this package monitor are:

ASSY SITE	PINS	PACKAGE		
ATP (Amkor, PI)	10	uSOP	ATP (Amkor, PI)	8 uSOP
ATP (Amkor, PI)	10	uSOP (Pb-Free)	ATP (Amkor, PI)	8 uSOP (Pb-Free)
ATP (Amkor, PI)	8	uSOP (Pb-Free) Exposed Pad	ATP (Amkor, PI)	8 uSOP Exposed Pad
Unisem	10	uSOP	Unisem	8 uSOP
Unisem	10	uSOP (Pb-Free)	Unisem	8 uSOP (Pb-Free)
Unisem	8	uSOP (Pb-Free) Exposed Pad	Unisem	8 uSOP Exposed Pad
UTL (NSEB) UTAC	10	uSOP	UTL (NSEB) UTAC	8 uSOP
UTL (NSEB) UTAC	10	uSOP (Pb-Free)	UTL (NSEB) UTAC	8 uSOP (Pb-Free)

The calculated failure rate for this assembly is:

FAILURE RATE: MTTF (YRS): 37719 FITS: 3.0

The parameters used to calculate this failure rate are as follows:

Cf: 60% Ea: 0.7 Tu: 25 °C

The reliability data follows. At the start of this data is a description of the assembly vehicle used to generate this reliability data. The next section is the detailed reliability data for each stress. The reliability data section includes the latest data available. This report covers data between 7/1/2006 and 6/30/2007.

Assembly Information:

Package Type: uSOP (Pb-Free) 3x0.85
 Flammability: UL 94-V0
 Moisture Sensitivity (JEDEC J-STD20A) Level 1
 Date Code Range: 0626 to 0712

MOISTURE SENSITIVITY LEVEL 1

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
ULTRASOUND	0626	DS2740	J-STD-020		8	0	
STORAGE LIFE			125C	24 HRS	8		
MOISTURE SOAK			85 C/85% R.H.	168 HRS	8		
CONVECTION REFLOW			260C +/-5C	3 PASS	8	0	
EXTERNAL VISUAL			J-STD-020, 6.1a		8	0	
PRECONDITION U/S			J-STD-020		8	0	
Total:						0	

OPERATING LIFE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
HIGH TEMP OP LIFE	0626	DS2740	125C, 5.5 VOLTS	1000 HRS	77	0	
HIGH TEMP OP LIFE	0629	DS2745	125C, 5.5 VOLTS	1000 HRS	77	0	
HIGH TEMP OP LIFE	0635	DS28EA00	125C, 5.5 VOLTS	1000 HRS	77	0	
HIGH TEMP OP LIFE	0702	MAX6618	125C, 3.6V (PSA) & 1.1V (PSB)	1000 HRS	45	0	
HIGH TEMP OP LIFE	0712	DS3904	125C, 5.5 VOLTS	1000 HRS	45	0	
Total:						0	

PACKAGE TESTS

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
SOLDERABILITY (Sn/Pb)	0626	DS2740	JESD22-B102, COND C		5	0	
SOLDERABILITY (Pb-Free)			JESD22-B102, COND C		5	0	
X-RAY	0626	DS2740	MIL-STD-883-2012 : TOP & SIDE VIEW		6	0	
PHYSICAL DIMENSIONS			JESD22-B100		6	0	
MARK PERMANENCY			JESD22-B107		6	0	
LEAD INTEGRITY			JESD22-B105, COND B		6	0	
					Total:	0	

PRECONDITIONING LEVEL 1

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
STORAGE LIFE	0626	DS2740	125C	24 HRS	385		
MOISTURE SOAK			85 C/85% R.H.	168 HRS	385		
CONVECTION REFLOW			260C +/-5C	3 PASS	385	0	
					Total:	0	

STORAGE LIFE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
STORAGE LIFE	0626	DS2740	150C	1000 HRS	77	0	
					Total:	0	

TEMPERATURE CYCLE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
TEMP CYCLE	0626	DS2740	-55C TO 125C	1000 CYS	77	0	
TEMP CYCLE	0629	DS2745	-55C TO 125C	1000 CYS	77	0	
					Total:	0	

TEMPERATURE HUMIDITY BIAS

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
HAST	0626	DS2740	130C, 85%R.H.,5.5V	100 HRS	77	0	
HAST	0629	DS2745	130C, 85%R.H.,5.5V	96 HRS	76	0	
					Total:	0	

UNBIASED MOISTURE RESISTANCE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
AUTOCLAVE	0626	DS2740	121C, 2 ATM STEAM, UNBIASED	168 HRS	77	0	
AUTOCLAVE	0629	DS2745	121C, 2 ATM STEAM, UNBIASED	168 HRS	77	0	
					Total:	0	

FAILURE RATE: MTTF (YRS): 37719 FITS: 3.0