



1/25/2008

RELIABILITY MONITOR REPORT
FOR

SSOP Package

MAXIM Integrated Products

120 San Gabriel Dr.
Sunnyvale, CA 94086

This Report was prepared by
Maxim Reliability Engineering

Summary:

The data in the tables that follow was generated as the result of an on-going Package Reliability Monitor. The specific assemblies included in this package monitor are:

ASSY SITE	PINS	PACKAGE
UNK	28	SSOP

The calculated failure rate for this assembly is:

FAILURE RATE: MTTF (YRS): 17247 FITS: 6.6

The parameters used to calculate this failure rate are as follows:

Cf: 60% Ea: 0.7 Tu: 25 °C

The reliability data follows. At the start of this data is a description of the assembly vehicle used to generate this reliability data. The next section is the detailed reliability data for each stress. The reliability data section includes the latest data available. This report covers data between and

Assembly Information:

Package Type: SSOP
Flammability: UL 94-V0
Date Code Range: 0633 to 0633

OPERATING LIFE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
HIGH TEMP OP LIFE	0633	MXL1544CAI+	135C, 5.25V	1000 HRS	44	0	
		MXL1544CAI	135C, 5.25V	1000 HRS	45	0	
				Total:		0	

FAILURE RATE: MTTF (YRS): 17247 FITS: 6.6