

4/17/2013



RELIABILITY MONITOR REPORT
FOR

CDIP Package

MAXIM INTEGRATED

160 RIO ROBLES
SAN JOSE, CA 95134

This Report was prepared by
MAXIM INTEGRATED Reliability Engineering

Summary:

The data in the tables that follow was generated as the result of an on-going Package Reliability Monitor. The specific assemblies included in this package monitor are:

ASSY SITE	PINS PACKAGE
ATP (Amkor, PI)	16 CDIP

The calculated failure rate for this assembly is:

FAILURE RATE: MTTF (YRS): 17440 FITS: 6.5

The parameters used to calculate this failure rate are as follows:

Cf: 60% Ea: 0.7 Tu: 25 °C

The reliability data follows. At the start of this data is a description of the assembly vehicle used to generate this reliability data. The next section is the detailed reliability data for each stress. The reliability data section includes the latest data available. This report covers data between 4/1/2012 and 3/31/2013.

Assembly Information:

Package Type: CDIP
Date Code Range: 1142 to 1143

OPERATING LIFE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
HIGH TEMP OP LIFE	1142	MAX232MJE/883B	135°C	1000 HRS	45	0	
HIGH TEMP OP LIFE	1143	MAX232MJE/883B	135°C	1000 HRS	45	0	
Total:						0	

STORAGE LIFE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
STORAGE LIFE	1143	MAX232MJE/883B	150°C	1000 HRS	77	0	
STORAGE LIFE	1143	MAX232MJE/883B	150°C	1000 HRS	77	0	
STORAGE LIFE	1143	MAX232MJE/883B	150°C	1000 HRS	77	0	
Total:						0	

TEMPERATURE CYCLE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
TEMP CYCLE, 5' RAMP, 10' DWELL	1143	MAX232MJE/883B	-65C TO 150C	1000 CYS	77	0	
TEMP CYCLE, 5' RAMP, 10' DWELL	1143	MAX232MJE/883B	-65C TO 150C	1000 CYS	77	0	
TEMP CYCLE, 5' RAMP, 10' DWELL	1143	MAX232MJE/883B	-65C TO 150C	1000 CYS	77	0	
Total:						0	

FAILURE RATE: MTTF (YRS): 17440 FITS: 6.5